



Rigid Coupling



Nominal Size mm/in	Pipe O.D mm/in	Working Pressure PSI/MPa	Bolt Size	Dimensions mm/in			
				No.-Size mm	Ø	L	H
25	33.7	300	2-M10*45	55.	95	45	
1	1.327	2.07		2.165	3.74	1.772	
32	42.4	300	2-M10*45	65	105	45	
1¼	1.669	2.07		2.559	4.133	1.772	
40	48.3	300	2-M10*45	71.	110	45	
1½	1.900	2.07		2.795	4.331	1.772	
50	60.3	300	2-M10*55	82	124	45	
2	2.375	2.07		3.228	4.882	1.772	
65	73.0	300	2-M10*55	98	141	45	
2½	2.875	2.07		3.858	5.551	1.772	
65	76.1	300	2-M10*55	100	142	45	
3OD	3.000	2.07		3.937	5.59	1.772	
80	88.9	300	2-M12*60	113	160	46	
3	3.500	2.07		4.449	6.299	1.811	
100	114.3	300	2-M12*65	142	190	49	
4	4.500	2.07		5.59	7.48	1.929	
125	139.7	300	2-M12*75	168	218	49	
5.5OD	5.500	2.07		6.614	8.583	1.929	
150	165.1	300	2-M12*75	194	244	49	
6.5OD	6.500	2.07		7.638	9.606	1.929	
150	168.3	300	2-M12*75	198	248	49	
6	6.625	2.07		7.795	9.764	1.929	
200	219.1	300	2-M16*100	256	320	60	
8	8.625	2.07		10.079	12.598	2.362	
250	273	300	2-M22*130	328	420	64	
10	10.748	2.07		12.913	16.535	2.52	
300	323.9	300	2-M22*130	380	454	64	
12	12.752	2.07		14.961	17.874	2.52	

Flexible Coupling



Nominal Size mm/in	Pipe O.D mm/in	Working Pressure PSI/MPa	Bolt Size	Dimensions mm/in			
				No.-Size mm	Ø	L	H
25	33.7	300	2-M10*45	55.	95	45	
1	1.327	2.07		2.165	3.74	1.772	
32	42.4	300	2-M10*45	65	105	45	
1¼	1.669	2.07		2.559	4.133	1.772	
40	48.3	300	2-M10*45	71.	110	45	
1½	1.900	2.07		2.795	4.331	1.772	
50	60.3	300	2-M10*55	82	124	45	
2	2.375	2.07		3.228	4.882	1.772	
65	73.0	300	2-M10*55	98	141	45	
2½	2.875	2.07		3.858	5.551	1.772	
65	76.1	300	2-M10*55	100	142	45	
3OD	3.000	2.07		3.937	5.59	1.772	
80	88.9	300	2-M12*60	113	160	46	
3	3.500	2.07		4.449	6.299	1.811	
100	114.3	300	2-M12*65	142	190	49	
4	4.500	2.07		5.59	7.48	1.929	
125	139.7	300	2-M12*75	168	218	49	
5.5OD	5.500	2.07		6.614	8.583	1.929	
150	165.1	300	2-M12*75	194	244	49	
6.5OD	6.500	2.07		7.638	9.606	1.929	
150	168.3	300	2-M12*75	198	248	49	
6	6.625	2.07		7.795	9.764	1.929	
200	219.1	300	2-M16*100	256	320	60	
8	8.625	2.07		10.079	12.598	2.362	
250	273	300	2-M22*130	328	420	64	
10	10.748	2.07		12.913	16.535	2.52	
300	323.9	300	2-M22*130	380	454	64	
12	12.752	2.07		14.961	17.874	2.52	